



LARGE SYNOPTIC SURVEY TELESCOPE

# Large Synoptic Survey Telescope (LSST) Characterization Metric Report: Science Pipelines Version 15.0

**Simon Krughoff and Michael Wood-Vasey**

**DMTR-62**

**Latest Revision: 2018-04-01**

## **Abstract**

This brief report describes measurements of interest that were carried out for release v15.0 of the Science Pipeline.

In short, the astrometric performance is excellent in comparison to both the per cycle ramps as well as the design level KPMs. The photometric performance is not as good. The inclusion of `jointcal` in the processing in future cycles will improve photometric performance. Current reprocessing of HSC data using a precursor to `jointcal` called `meas_mosaic` shows significant improvement over single epoch processing.

The report for the previous version can be found in DMTR-41.



## Contents

|                                    |          |
|------------------------------------|----------|
| <b>1 Photometric Performance</b>   | <b>1</b> |
| <b>2 Astrometric Performance</b>   | <b>2</b> |
| <b>3 Ellipticity Correlations</b>  | <b>3</b> |
| <b>4 Computational Performance</b> | <b>4</b> |

# Characterization Metric Report: Science Pipelines Version 15.0

Measured using `validation_data_hsc`, which consists of 8 HSC engineering images: 2 *r*-band, 4 *i'*-band, and 2 *y*-band. Measurements were made on individual, separately-processed, single-frame images: `Jointcal` and/or `meas_mosaic` were not run. For comparison, we provide the SRD required “design” value of each metric as defined in the Science Requirements Document [LPM-17], and, where available, the target for this release as defined in the Data Management Development Milestone Roadmap [LDM-240]. All values were computed using the `examples/runHscTest.sh` script in the `validate_drp` package.

Some KPMs (AF1, AD1) involve thresholds that are different for “design”, “minimum”, and “stretch” specifications. Thus comparing one of these metrics against a given target number is a two-level process. Both the threshold used in the calculation is dependent on the specifications, and the requirement on the computed number is dependent on the specifications.

The metrics in this report have all been computed relative to the “design” thresholds. The values of these KPMs would be different if computed against different thresholds.

Note also that the photometric performance of the pipelines in the *y*-band is an under estimate of expected delivered performance. For these tests, the *y*-band data was calibrated with *z*-band photometry. This is due to the lack of a reference catalog containing *y*-band information at this time. We recognize that the bandpass mismatch is certainly not the only source of scatter in the *y*-band photometry. These metric measurements are still worth noting in this report as a historical benchmark to track relative performance.

The per cycle target numbers come from the “KPMs” sheet of LDM-240.

## 1 Photometric Performance

*Submitted by Simon Krughoff and Michael Wood-Vasey*

`procCalRep` corresponds to requirement OSS-REQ-0275 (defined in LSE-30). All other photometric performance metrics follow LSS-REQ-0093 (LSE-29) and LPM-17 table 14.

| Metric        | Unit | SRD                    |                      | Value | Comments         |
|---------------|------|------------------------|----------------------|-------|------------------|
|               |      | Requirement-<br>Design | Release 15<br>Target |       |                  |
| procCalRep    | mmag | $\leq 13$              | —                    | —     | Need simulations |
| PA1: <i>u</i> | mmag | $\leq 12$              | —                    | —     | No data          |
| PA1: <i>g</i> | mmag | $\leq 8$               | —                    | —     | No data          |
| PA1: <i>r</i> | mmag | $\leq 5$               | 8.0                  | 14.60 |                  |
| PA1: <i>i</i> | mmag | $\leq 5$               | 8.0                  | 11.99 |                  |
| PA1: <i>z</i> | mmag | $\leq 12$              | —                    | —     | No data          |
| PA1: <i>y</i> | mmag | $\leq 12$              | 12.0                 | 25.07 |                  |
| PF1: <i>u</i> | %    | $\leq 20$              | —                    | —     | No data          |
| PF1: <i>g</i> | %    | $\leq 20$              | —                    | —     | No data          |
| PF1: <i>r</i> | %    | $\leq 10$              | 10.0                 | 31.72 |                  |
| PF1: <i>i</i> | %    | $\leq 10$              | 10.0                 | 26.55 |                  |
| PF1: <i>z</i> | %    | $\leq 20$              | —                    | —     | No data          |
| PF1: <i>y</i> | %    | $\leq 20$              | 20.0                 | 37.23 |                  |
| PA2: <i>u</i> | mmag | $\leq 22.5$            | —                    | —     | No data          |
| PA2: <i>g</i> | mmag | $\leq 15$              | —                    | —     | No data          |
| PA2: <i>r</i> | mmag | $\leq 15$              | 20.0                 | 27.22 |                  |
| PA2: <i>i</i> | mmag | $\leq 15$              | 20.0                 | 25.42 |                  |
| PA2: <i>z</i> | mmag | $\leq 22.5$            | —                    | —     | No data          |
| PA2: <i>y</i> | mmag | $\leq 22.5$            | 20.0                 | 44.56 |                  |

## 2 Astrometric Performance

*Submitted by Simon Krughoff and Michael Wood-Vasey*

The following metrics are defined following LSR-REQ-0094 [LSE-29] and LPM-17 table 18.

| Metric        | Unit | SRD Requirement | Release 15 Target | Value |
|---------------|------|-----------------|-------------------|-------|
| AM1: <i>r</i> | mas  | $\leq 20$       | 30.0              | 6.67  |
| AM1: <i>i</i> | mas  | $\leq 20$       | 30.0              | 9.08  |
| AM1: <i>y</i> | mas  | $\leq 20$       | 30.0              | 12.45 |

| Metric        | Unit | SRD Requirement | Release 15 Target | Value |
|---------------|------|-----------------|-------------------|-------|
| AF1: <i>r</i> | %    | $\leq 10$       | 10.0              | 2.64  |
| AF1: <i>i</i> | %    | $\leq 10$       | 10.0              | 2.16  |
| AF1: <i>y</i> | %    | $\leq 10$       | 10.0              | 10.72 |
| AD1: <i>r</i> | mas  | $\leq 20$       | 20.0              | 10.89 |
| AD1: <i>i</i> | mas  | $\leq 20$       | 20.0              | 10.91 |
| AD1: <i>y</i> | mas  | $\leq 20$       | 20.0              | 20.80 |
| AM2: <i>r</i> | mas  | $\leq 10$       | 40.0              | 6.46  |
| AM2: <i>i</i> | mas  | $\leq 10$       | 40.0              | 9.90  |
| AM2: <i>y</i> | mas  | $\leq 10$       | 40.0              | 13.17 |
| AF2: <i>r</i> | %    | $\leq 10$       | 10.0              | 2.24  |
| AF2: <i>i</i> | %    | $\leq 10$       | 10.0              | 2.26  |
| AF2: <i>y</i> | %    | $\leq 10$       | 10.0              | 11.11 |
| AD2: <i>r</i> | mas  | $\leq 20$       | 20.0              | 10.59 |
| AD2: <i>i</i> | mas  | $\leq 20$       | 20.0              | 11.02 |
| AD2: <i>y</i> | mas  | $\leq 20$       | 20.0              | 21.29 |

### 3 Ellipticity Correlations

*Submitted by Simon Krughoff and Michael Wood-Vasey*

The following metrics are defined following LSR-REQ-0097 [LSE-29] and LPM-17 table 27.

| Metric        | Unit | SRD Requirement         | Release 15 Target       | Value                 |
|---------------|------|-------------------------|-------------------------|-----------------------|
| TE1: <i>r</i> | —    | $\leq 3 \times 10^{-5}$ | $\leq 3 \times 10^{-5}$ | $3.37 \times 10^{-6}$ |
| TE1: <i>i</i> | —    | $\leq 3 \times 10^{-5}$ | $\leq 3 \times 10^{-5}$ | $1.12 \times 10^{-6}$ |
| TE1: <i>y</i> | —    | $\leq 3 \times 10^{-5}$ | $\leq 3 \times 10^{-5}$ | $5.92 \times 10^{-5}$ |
| TE2: <i>r</i> | —    | $\leq 3 \times 10^{-7}$ | $\leq 3 \times 10^{-7}$ | $8.30 \times 10^{-8}$ |
| TE2: <i>i</i> | —    | $\leq 3 \times 10^{-7}$ | $\leq 3 \times 10^{-7}$ | $1.27 \times 10^{-7}$ |
| TE2: <i>y</i> | —    | $\leq 3 \times 10^{-7}$ | $\leq 3 \times 10^{-7}$ | $6.82 \times 10^{-7}$ |

## 4 Computational Performance

Computational performance metrics were not re-measured for this release. We expect no significant changes relative to the report on version 12 [DMTR-15].

### References

- [1] **[LSE-29]**, Claver, C.F., The LSST Systems Engineering Integrated Project Team, 2017, *LSST System Requirements (LSR)*, LSE-29, URL <https://ls.st/LSE-29>
- [2] **[LSE-30]**, Claver, C.F., The LSST Systems Engineering Integrated Project Team, 2018, *Observatory System Specifications (OSS)*, LSE-30, URL <https://ls.st/LSE-30>
- [3] **[LPM-17]**, Ivezić, Ž., The LSST Science Collaboration, 2011, *LSST Science Requirements Document*, LPM-17, URL <https://ls.st/LPM-17>
- [4] **[LDM-240]**, Kantor, J., Jurić, M., Lim, K.T., 2016, *Data Management Releases*, LDM-240, URL <https://ls.st/LDM-240>
- [5] **[DMTR-41]**, S. Krughoff, J.W.V., 2017, *Characterization Metric Report: Science Pipelines Version 14.0*, DMTR-41, URL <https://ls.st/DMTR-41>
- [6] **[DMTR-15]**, Wood-Vasey, M., Swinbank, J., 2017, *Characterization Metric Report: Science Pipelines Version 13.0*, DMTR-15, URL <https://ls.st/DMTR-15>